



**Graffiti Remover**

Ecological cleaner for most types of paint and graffiti

**Interior & exterior use**

A low odour non caustic treatment for most types of ink or paint-based graffiti. Removes most spray paint from concrete, clinker, brick, glazed tiles, rendering, wood and other porous surfaces except painted or plastic/acrylic.

**Directions for use**

**Preparation:**

Ensure surface to be treated is completely clean and free from atmospheric pollution. First wash surfaces with

**Eco Pro Tec Stone & Tile Intensive Cleaner.** Organic matter including moss and algae should be cleaned using **Eco Pro Tec Paving Cleaner.** Rinse well with water to finish.

**Cleaning:**

Always test on a small hidden portion of the substrate before applying.

**Surfaces protected with Eco Pro Tec Anti-Graffiti Sealer:**

Shake bottle before use. Apply generously and evenly using a roller or paint brush. Wait until the paint has softened (typically 10– 20 mins). Scrub well using a stiff brush or emulsifying pad and rinse well with plenty of water.

**Similar Un-protected surfaces:** Shake bottle before use. Apply to dampened surfaces. In the case of porous surfaces especially, pre-wetting the surface with water will prevent the dissolved paint from seeping any deeper into the surface.

Apply generously and evenly using a roller or paint brush. Wait until the paint has dissolved (30 mins). Scrub well using a stiff brush or emulsifying pad and rinse well with plenty of water. If residues or paint traces are still visible, repeat the operation.

On vertical surfaces apply from the top down.

**Coverage: M<sup>2</sup> per application**

|                  | 1 LTR            | 5 LTR            | 25 LTR |
|------------------|------------------|------------------|--------|
| Surface cleaning | 10m <sup>2</sup> | 50m <sup>2</sup> | N/A    |
| Deep stripping   | 5m <sup>2</sup>  | 25m <sup>2</sup> | N/A    |
| In extreme cases | 3m <sup>2</sup>  | 15m <sup>2</sup> | N/A    |

**Storage information**

Store in a cool, dry, frost free environment  
Shelf life up to 2 years for un-opened containers

**Other**

Do not apply during rain, frost, or when surface and air temp is under 5°C or over 30°C. Use gloves and protective goggles if there is a risk of direct contact or splashing.

Empty containers are recyclable.

Clean application tools and brushes with water after use.

Once cleaned protect with Eco Pro Tec Anti-Graffiti Sealer

**Health, Safety & Environmental**

CONTAINS: benzyl alcohol, alcohol ethoxylate

**Harmful if swallowed**

**Harmful if inhaled.**

Keep out of reach of children. Avoid breathing fume, vapours, mist. Wash hands and other exposed areas thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area.

**IF SWALLOWED:** Call a doctor a **POISON CENTRE** if you fill unwell. **IF INHALED:** Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel unwell. Rinse mouth.

Dispose of contents/container to a licensed waste centre in accordance with local/regional/national/international regulations.



**WARNING**



*This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area*

